

What is claimed is:

1 1. An apparatus comprising:

2 a sleeve sized to receive a bar, the sleeve comprising a nub; and

3 a movable assembly comprising a spindle and a bracket, the bracket sized to fit over  
 4 either of the bar and the nub.

5

1 2. The apparatus of claim 1, the movable assembly further comprising:

2 a drive axle coupled by way of gears to the spindle, the gears configured to amplify a  
 3 torque applied to the drive axle and to apply the amplified torque to turn the spindle.

4

1 3. The apparatus of claim 2 further comprising:

2 the movable assembly configured for mounting a power drill with a chuck of the power  
 3 drill positioned to receive the drive axle.

4

1 4. The apparatus of claim 1, the bar and the sleeve further comprising holes which when  
 2 aligned may receive a pin to secure the bar within the sleeve.

3

1 5. The apparatus of claim 1 in which the sleeve is sized to receive the bar of a standard  
 2 trailer hitch.

3

1 6. The apparatus of claim 4, the nub and the bracket further comprising holes which  
 2 when aligned may receive a pin to secure the movable assembly to the nub.

3

1 7. An apparatus comprising:

2 a boom comprising at least one bar and sleeve; and

3 a movable spindle;

4 wherein the sleeve is adapted to receive an end of the bar, and both the sleeve and the bar  
 5 are adapted to mount the movable spindle.

6

1 8. The apparatus of claim 7 wherein the sleeve comprises a nub having a width  
 2 substantially the same as the width of the bar, and wherein the movable spindle  
 3 comprises a mount sized to receive a width of either of the bar and the nub.

4

1 9. The apparatus of claim 7 wherein the movable spindle comprises a drive axle and  
 2 gears to step up a torque applied to the drive axle to turn the spindle.

3

1 10. The apparatus of claim 7 wherein the drive axle is adapted to receive the chuck of a  
 2 power drill.

3

1 11. An apparatus comprising:

2 a sleeve sized to receive a bar, the sleeve comprising a nub;

3 a movable gearbox assembly comprising a mount to receive a power drill and a bracket

4 sized to fit over either of the bar and the nub;

5 a mechanism to depress <sup>NA</sup>(the power switch) of the power drill when the power drill is

6 mounted to the gearbox assembly; and

7 a foot pedal assembly to couple the power drill to a power source when the foot pedal is  
8 operated.

9

1 12. The apparatus of claim 11 further comprising:

2 a base assembly comprising a pivot for setting the angle of a boom, the boom comprising  
3 at least one bar and sleeve.

4

5 13. An apparatus comprising:

6 a base assembly comprising a pivotable base bar;

7 a boom comprising a sleeve to receive an end of the base bar at a first end and to receive

8 an end of (the <sup>NA</sup> extension bar) at a second end, the sleeve comprising a nub having

9 substantially the same width as the extension bar; and

10 a movable spindle assembly adapted to mount over either the extension bar or the nub of  
11 the sleeve.

12

1 14. The apparatus of claim 1 further comprising:

2 a foot pedal which, when operated, provides power to a torque source to turn the spindle.

3

1 15. The apparatus of claim 1 further comprising:

2 a first pulley assembly coupled to the boom and a second pulley assembly coupled to the

3 first pulley assembly, the first pulley assembly comprising a first pulley axle substantially

4 orthogonal to a second pulley axle of the second pulley assembly.

5

- # CONFIDENTIAL